

TECHNOLOGY	Single Driver Dual Embedded Transmission Line ETL™		
FREQUENCY RESPONSE	70Hz -20 kHz (-6db)		
POWER HANDLING	20 W RMS (100W IHF with 70Hz HPF)		
DRIVER COMPLIMENT	Single 3 inch full-range paper cone (low gauss magnet) May be placed close to CRT television monitors		
IMPEDANCE	8 ohms nominal		
SENSITIVITY	87db 1w @1m		
DISTORTION	less than 1% 100Hz to 20Khz 3W input (It is recommended to use active or passive crossover when operated at maximum power). Optimal crossover point is 70 Hz		
DIMENSIONS/WEIGHT	4.625" W x 5.5" H x 5.125" D (with grille in place) - 2lbs		
MOUNTING	1/4 - 20 standard threads for most wall or stand mounts		
CONNECTION	Gold 5 Way binding posts		
FINISH	MD-1BT (Textured black)		
	MD-1BM (Matte black)		
	MD-1BG (Gloss black)		
	MD-1WG (Gloss Pearlescent white)		
SUGGESTED APPLICATIONS	High End Quality Stand mount Monitors		
	Plasma/LCD Wall Mount Audio Monitors		
	Close Recording Console Audio Monitoring		
	Mobile On Location Recording		
	5.1 Channel Surround Sound		
PRICE (per pair)	MPEG Playback (When used with Optional Amplifier)		
	Bass fill for electrostatic/ribbons/dynamic planar 80 Hz -200 Hz and higher		
	Black Textured	MD-1BT	\$400.00 (USD) per pair
	Black Matte	MD-1BM	\$400.00 (USD) per pair
	Black Gloss	MD-1BG	\$450.00 (USD) per pair
	White Gloss	MD-1WG	\$450.00 (USD) per pair (pearlescent)